

Issue Date 02-Dec-2015

Revision Date 02-Dec-2015

Version 1

1. IDENTIFICATION

Product identifier

Product Name 790-11EV HOT RUBBERIZED ASPHALT

Other means of identification

Product Code BH79011E

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Waterproofing Sealers

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

HENRY COMPANY

999 N. Sepulveda Blvd., Suite 800

El Segundo, CA 90245-2716

Web Site: www.henry.com www.ca.henry.com

Emergency telephone number

Company Phone Number 800-486-1278

Emergency Telephone CHEMTREC: 800-424-9300

CHEMTREC: 703-527-3887

CANUTEC: 613-966-6666

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3

Label elements

Emergency Overview

Warning

Hazard statements

Causes skin irritation

Causes serious eye irritation

May cause respiratory irritation



Appearance No information available**Physical state** Solid**Odor** Sulfurous**Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling
Wear protective gloves/protective clothing/eye protection/face protection
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
IF ON SKIN: Wash with plenty of soap and water
If skin irritation occurs: Get medical advice/attention
Take off contaminated clothing and wash before reuse
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a POISON CENTER or doctor/physician if you feel unwell

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed
Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

CONTACT WITH HOT PRODUCT WILL CAUSE THERMAL BURNS.

3. COMPOSITION/INFORMATION ON INGREDIENTS**Substance**

Chemical Name	CAS No	Weight-%
Asphalt *	8052-42-4	15 - 40
Limestone *	1317-65-3	15 - 40
Distillates, petroleum, hydrotreated heavy naphthenic *	64742-52-5	10 - 30
Polymer Blend *	Proprietary	1 - 5
Sulfur *	7704-34-9	1 - 5

*The exact percentage (concentration) of composition has been withheld as a trade secret.

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

4. FIRST AID MEASURES**Description of first aid measures****General advice**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). If symptoms persist, call a physician.

Eye contact

Keep eye wide open while rinsing. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. If symptoms persist, call a physician.

Skin contact

Removal of solidified molten material from skin requires medical assistance. In case of burns, immediately cool affected skin for as long as possible with cold water. For severe

burns, immediate medical attention is required.

Inhalation

Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If symptoms persist, call a physician.

Ingestion

Call a physician or poison control center immediately. Do not induce vomiting without medical advice. Rinse mouth. Never give anything by mouth to an unconscious person.

Self-protection of the first aider

Remove all sources of ignition. Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed**Symptoms**

May cause redness and tearing of the eyes. Coughing and/ or wheezing. May cause skin irritation. Drowsiness. Dizziness.

Indication of any immediate medical attention and special treatment needed**Note to physicians**

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

CO2, dry chemical, dry sand, alcohol-resistant foam.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating and toxic gases and vapors.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures**Personal precautions**

Wear protective gloves/protective clothing and eye/face protection. Ensure adequate ventilation, especially in confined areas.

Environmental precautions**Environmental precautions**

Do not allow into any sewer, on the ground or into any body of water.

Methods and material for containment and cleaning up**Methods for containment**

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling**Advice on safe handling**

Use personal protective equipment as required. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate

ventilation, especially in confined areas. Avoid breathing fumes from hot material.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Keep away from heat.

Incompatible materials Strong oxidizing agents. Strong acids.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Asphalt 8052-42-4	TWA: 0.5 mg/m ³ benzene soluble aerosol fume, inhalable fraction	-	Ceiling: 5 mg/m ³ fume 15 min
Limestone 1317-65-3	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust

NIOSH IDLH Immediately Dangerous to Life or Health

Appropriate engineering controls

Engineering Controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective gloves and protective clothing.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Solid	Odor	Sulfurous
Appearance	No information available	Odor threshold	No information available
Color	black		
Property	Values	Remarks • Method	
pH	No information available		
Melting point / freezing point	No information available		
Boiling point / boiling range	No information available		
Flash point	291 °C / 556 °F	Cleveland Open Cup	
Evaporation rate	No information available		
Flammability (solid, gas)	No information available		
Flammability Limit in Air			
Upper flammability limit:	No information available		
Lower flammability limit:	No information available		
Vapor pressure	No information available		
Vapor density	No information available		
Relative density	0.9-1.2		
Water solubility	Insoluble in water		
Solubility in other solvents	No information available		

Partition coefficient	No information available
Autoignition temperature	>290 °C / >550 °F
Decomposition temperature	No information available
Kinematic viscosity	No information available
Dynamic viscosity	No information available
Explosive properties	Not an explosive
Oxidizing properties	Not applicable

Other Information

Softening point	No information available
Molecular weight	No information available
VOC Content (%)	No information available
Density	No information available
Bulk density	No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous polymerization	Hazardous polymerization does not occur.
---------------------------------	--

Conditions to avoid

Incompatible materials. To avoid thermal decomposition, do not overheat.

Incompatible materials

Strong oxidizing agents. Strong acids.

Hazardous Decomposition ProductsCarbon monoxide. Carbon dioxide (CO₂). Hydrogen sulfide.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure**Product Information**

Inhalation	May cause irritation of respiratory tract.
Eye contact	Irritating to eyes.
Skin contact	Irritating to skin. Contact with product at elevated temperatures can result in thermal burns.
Ingestion	No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Asphalt 8052-42-4	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
Sulfur 7704-34-9	> 3000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 9.23 mg/L (Rat) 4 h

Information on toxicological effects

Symptoms	May cause redness and tearing of the eyes. Coughing and/ or wheezing. May cause skin irritation.
-----------------	--

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization	No information available.
----------------------	---------------------------

**Germ cell mutagenicity
Carcinogenicity**

No information available.

An analysis of cancer studies in humans suggests an association between lung cancer and exposure to hard bitumens during roofing and mastic asphalt work. The majority of animal studies of oxidized asphalt have been negative in dermal cancer studies, however a two-year study in mice exposed to fume condensates of severely oxidized asphalt caused a weak, but statistically significant increase in skin tumors. The International Agency for Research on Cancer (IARC) published a preliminary finding in late 2011 indicating that occupational exposures to asphalts and their emissions during roofing and mastic asphalt work present a potential cancer risk to humans. Product containing mineral oil with less than 3% DMSO extract as measured by IP 346. The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Asphalt 8052-42-4	-	Group 2B	-	X
Distillates, petroleum, hydrotreated heavy naphthenic 64742-52-5	A2	Group 1	-	X
Polymer Blend	-	Group 3	-	-

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Not classifiable as a human carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

**Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
Target Organ Effects
Aspiration hazard**

No information available.

Respiratory system.

No information available.

Eyes, Respiratory system, Skin.

No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

Oral LD50 9225 mg/kg

Dermal LD50 4498 mg/kg

12. ECOLOGICAL INFORMATION**Ecotoxicity**

None known

Persistence and degradability

No information available.

Bioaccumulation

Chemical Name	Partition coefficient
Asphalt 8052-42-4	6

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS**Waste treatment methods****Disposal of wastes**

Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging

Do not reuse container.

14. TRANSPORT INFORMATION**DOT** Not regulated**TDG** Not regulated**IATA** Not regulated**IMDG** Not regulated**15. REGULATORY INFORMATION****International Inventories****TSCA** Complies**DSL/NDSL** Complies**EINECS/ELINCS** Complies**IECSC** Complies**KECL** Complies**PICCS** Complies**AICS** Complies**Legend:****TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances**ENCS** - Japan Existing and New Chemical Substances**IECSC** - China Inventory of Existing Chemical Substances**KECL** - Korean Existing and Evaluated Chemical Substances**PICCS** - Philippines Inventory of Chemicals and Chemical Substances**AICS** - Australian Inventory of Chemical Substances**US Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Quartz - 14808-60-7	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Asphalt 8052-42-4	X	X	X
Limestone 1317-65-3	X	X	X
Sulfur 7704-34-9	X	X	X
Quartz 14808-60-7	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION
--

NFPA	Health hazards 2	Flammability 1	Instability 0	Physical and Chemical Properties -
HMIS	Health hazards 2	Flammability 1	Physical hazards 0	Personal protection X

Issue Date 02-Dec-2015

Revision Date 02-Dec-2015

Revision Note

No information available

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet